GM Data Interface 2006-2012
AXADBXH-GM2

INTRODUCTION

The AXADBXH-GM2 harness is designed for, and must be used with, the AXADBX-1 or AXADBX-2 interface (sold separately). Please refer to the AXADBX-1 or AXADBX-2 for the 16-pin connector with stripped leads.

INTERFACE FEATURES

- Provides accessory power (12-volt 10-amp)
- Maintains the retained accessory power (R.A.P.) feature
- Provides NAV outputs (parking brake, reverse, speed sense)
- Retains chimes
- Retains OnStar / OE Bluetooth
- Adjustable OnStar level
- Retains the factory AUX-IN jack
- Retains satellite radio
- Pre-wired AXSWC harness (AXSWC sold separately)
- Can be used in non-amplified or amplified models
- Retains balance and fade

INTERFACE COMPONENTS

• AX-ADGM02 harness • 4-pin to 4-pin resistor pad harness

APPLICATIONS

CHEVROLET		PONTIAC		SATURN	
Cobalt	2007-2010	G5	2007-2009	Aura	2007-2009
HHR	2006-2011	G6*	2009	Sky	2007-2009
Malibu	2008-2012	G6	2010		
		Solstice	2006-2009		

5th digit of VIN must be a J, K, or L