# GM/Suzuki 2006-up AXVI-2105

GM LAN 29 accessory and NAV output interface

#### APPLICATIONS

BUICK		Tahoe	20
Enclave	2008-up	Traverse	
Lucerne	2006-2011	GMC	
CADILLAC		Acadia	
DTS	2006-2011	Savanna	
(only to be us	sed when replacing	Sierra (new body)	)
ai	n amplified system)	Sierra 2500/350	0
Escalade	2007-2014	Yukon/XL	20
	sed when replacing	HUMMER	
	n amplified system)	H2	2
SRX	2007-2009		
	sed when replacing	PONTIAC	
a	n amplified system)	Torrent	20
CHEVROLET		SATURN	
Avalanche	2007-up*	Outlook	20
Captiva Sport	2012-up	Vue	20
Cheyenne	2012-up *	SUZUKI	
Equinox	2007-2009	XL-7	20
Express	2008-up		
Impala	2006-2013	*Non n	ouidation m
Impala limited	2014	"IVO/1-//a	avigation m
Monte Carlo	2006-2007		
Silverado (new body)	2007-13*		
Silverado 2500/3500	) 2014 *		
Suburban	2007-2014*		

Tahoe	2007-2014*			
Traverse	2009-up			
GMC				
Acadia	2007-up			
Savanna	2008-up			
Sierra <i>(new body)</i>	2007-13*			
Sierra 2500/3500	2014*			
Yukon/XL	2007-2014*			
HUMMER				
H2	2008-2009			
PONTIAC				
Torrent	2007-2009			
SATURN				
Outlook	2007-2010			
Vue	2008-2010			
SUZUKI				
XL-7	2007-2009			
*Non-navigation models only				

### **KIT FEATURES**

- Provides accessory (12 volt 10 amp)
- Retains R.A.P. (retained accessory power)
- · Used in non-amplified systems or when replacing amplified system
- Provides NAV outputs (parking brake, reverse, and V.S.S.)
- Prewired AXSWC harness included (AXSWC sold separately)
- High level speaker input
- USB updatable

Note: All chimes will be lost when using this harness

# WIRING THE AXVI-2105

- Connect the Yellow wire to the radio's 12 volt battery or memory wire.
- · Connect the Black wire to the radio's ground wire.
- Connect the **Red** wire to the ignition wire of the aftermarket radio.
- · Connect the Orange wire to the illumination wire of the aftermarket radio. If the aftermarket radio has no illumination wire, tape off the **Orange** wire.
- Connect the **Blue** wire to the antenna turn on wire of the aftermarket radio
- · Connect the White wire to the left front positive speaker output of the aftermarket radio.
- Connect the White/Black wire to the left front negative speaker output of the aftermarket radio
- Connect the Gray wire to the right front positive speaker output of the aftermarket radio.

(continued on next page)

## AXVI-2105



- Connect the Gray/Black wire to the right front negative speaker output of the aftermarket radio.
- Connect the Green wire to the radio's left rear positive speaker output.
- Connect the Green/Black wire to the radio's left rear negative speaker output. ٠
- Connect the **Purple** wire to the radio's right rear positive speaker output. ٠
- Connect the Purple/Black wire to the radio's right rear negative speaker output.

The following wires are for the aftermarket radios that have navigation built in.

- Connect the Light Green wire to the parking brake wire of the aftermarket navigation radio (if applicable).
- Connect the Blue/Pink wire to the VSS or speed sense wire of the aftermarket navigation radio (if applicable).
- · Connect the Green/Purple wire to the reverse wire of the aftermarket navigation radio (if applicable).
- Cycle the key, by turning the ignition on for 30 seconds. Then off and on again to test the radio.

### AXSWC (if installing)

After the interface is initialized, plug in the AXSWC into the 12-pin harness of the AXVI-2105 and refer to the AXSWC instructions.

## IMPORTANT WARNING

This product includes instructions for installation which must be carefully followed. The instructions are worded in such a manner to assume that the installer is capable of completing these type of electronic installations. If you are unclear as to what you are instructed to do or believe that you do not understand the instructions so as to properly and safely complete the installation vou should consult a technician who does have this knowledge and understanding.

Failure to follow these instructions carefully and to install the interface as described could cause harm to the vehicle or to safety systems on the vehicle. Interference with certain safety systems could cause harm to persons as well. If you have any questions in this regard please call the Help line or Metra at 1-800-221-0932 for assistance.



KNOWLEDGE IS POWER Enhance your installation and fabrication skills enrolling in the most recognized and respected 800-354-6782 for more information and take st

