



## TE-GTGCHD (CCD) / TE-GTGC (CMOS)

### CHEVY SILVERADO & GMC SIERRA 1500 (2007-2013) CHEVY SILVERADO & GMC SIERRA 2500/3500 (2007-2014)

#### Replacement Tailgate Handle with Camera\*

*\*Camera is slightly offset to left by design.*

#### Removal and Installation Instructions

**Tools Needed:** 13mm wrench/13mm socket and ratchet

1. Start by lowering the tailgate. Stand and face the back end of the truck there will see three bolts, remove the two bolts that are side by side directly in front of you. Those bolts secure the tailgate handle to the tailgate.
2. Now close tailgate, carefully lift the factory tailgate handle out and away from the tailgate.
3. Now that the handle is out of the tailgate, you will have to swap the locking mechanism out of the old handle to the new one.
4. Route the backup camera's wires through the tailgate handle's opening and through the tailgate itself.  
**NOTE:** Avoid pinch points and things that can damage wires and their functions.
5. Remove tail light and splice the red camera wire into the reverse light's 12v positive wire this will trigger the camera to turn on when vehicle is placed in reverse. Attach the black ground wire to a metal non-painted surface.
6. Wires can now be fully routed from the tailgate to the cab of the truck and to a video source. Red

wire goes to the rear camera input trigger wire on your video source, plug RCA to your video screen input

**NOTE:** Test to make sure video is working before securing new handle.

7. Carefully replace new tailgate handle in tailgate and secure the handle using the three bolts that were previously removed.

**NOTE:** To disable parking lines, cut white wire loop.

To enable PAL mode, cut the blue wire loop.



1.800.221.0932

[www.iBeamUSA.com](http://www.iBeamUSA.com)

460 Walker Street, Holly Hill, FL 32117