



Chasing LED Motorcycle Expansion Pack 4-Piece

** LED strips will not adhere to any surface that has been treated with a ceramic coating. Either select alternate locations that are not treated, or enlist a professional to remove the ceramic coating from mounting locations before installation.*

Visit [MetraOnline.com](https://www.MetraOnline.com) to view the available installation parts and accessories. Watch a Complete Installation of this product on: [youtube.com](https://www.youtube.com)



Part Components

- (4) 4" Chasing LED strips with 3M adhesive backing
- (2) Adhesive promoter

Product Features


- Expand your Saddle Tramp® chasing LED lighting kit on any motorcycle with this convenient 4-piece expansion pack. Simply connect the included chasing LED strips to your existing chasing LED lighting kit and enjoy an expanded display with endless customization. These durable strips are IP67-rated and feature a 3M double-sided backing for easy installation. They work with your existing kit's Heise Connect Chasing Controller so that the lights can be remotely controlled using the free downloadable Heise Connect mobile app for smartphones and tablets. The app allows users to choose from 170+ color-changing patterns, a turn signal and brake function, a DIY pattern function, a music sync function, and more

Tools Needed

- Alcohol wipes
- Cable ties
- Side cutters

What's in the box:

- (A) LED strips
- (B) Accessories




- There are 4 identical strips, locate 2 places on the clutch side of the bike to place the lights. If more locations are desired, additional BC-CHASE-4PC can be added (sold separately).
- Clean the first location with alcohol, apply adhesion promoter, peel the protective backing from the strip, and press the strip into place with the arrows on the strip pointing away from the controller. Repeat for second location.



- Use Y cables and extensions (not included) to connect strips to existing kit. Route cables, avoiding moving parts, hot surfaces, and pinch points. Make sure to secure cable and any excess.

* Clutch side lights should be connected to the controller "Left" output, and Brake side lights to the "Right" output.

* The output wire on the last strip of a run can be cut off for a cleaner installation. Apply silicone to seal the cut end.



- Repeat for the brake side.
- Test your entire lighting system.

Having difficulties? We're here to help.



Contact our Tech Support line at:
386-257-1187



Or via email at:
techsupport@metra-autosound.com

Tech Support Hours (Eastern Standard Time)

Monday - Friday: 9:00 AM - 7:00 PM
Saturday: 10:00 AM - 5:00 PM
Sunday: 10:00 AM - 4:00 PM